

Alerta® Brand AFM 30 - 50 as Fire Fighting Monitor, it provides good long jet range and stable quality, the fire monitor nozzle flow rate from 1800 LPM up to 3000 LPM. Firefighting Equipment Manufacturer A lightweight and highly durable flow-efficient monitor due to the Aluminum Alloy with Hard Anodized with few and easy maintenance, suitable for good of industries.

FEATURES

- Light aluminum alloy construction
- Elevation travel of 135°, From -45° To +90°
- 360° Rotation Horizontally
- Stainless steel handle tiller control
- Nozzle has a built-in Stream Sharper
- Available for straight stream and Fog pattern
- Long service and easy repair
- Liquid-filled pressure gauge
- Complete with elevation locking device
- Flow rate from 1800 LPM up to 3000 LPM
- Water Jetting Range: Max 65 meters
- Working pressure: 10 bar (1.0 MPa)
- Weight: 15.2kg
- Carton package: 16.5kg/70*38.5*28cm
- Color: Red standard



1800-3000LPM
Stacked tips nozzle
Detachable each parts

4" BS 4504 Flange is standard Thread
inlet, other sizes & std. are available



Level Hand

Oiled Pressure Gauge

Elevation Locking Device

MATERIAL

Body	Hard Anodized Aluminum Alloy
Nozzle	Hard Anodized Aluminum Alloy
Stream Sharper	Hard Anodized Aluminum Alloy
Handle	Stainless Steel

APPLICATION

- Refineries
- Fuel distribution depots
- Chemical plants
- Warehouses
- Helicopter landing pads
- Aircraft hangars
- Loading jetties
- Process plants
- Industrial process areas
- Shipping Vehicle-mounted

Model	PS30-50
Flow Rate	1800-3000LPM (Selectable flow nozzle)
Working Pressure	1.0 MPa
Water Jetting Range	≥ 65 meters
Max. Fog Angle	120°
Horizontal Rotation Angle	0-360°
Elevation Rotation Angle	-45° - +90°
Waterway Size	2.5" (65mm)
Outlet	2.5" Male Thread
Inlet	4" BS 4504 Flange is standard (Thread inlet, other sizes & std. are available)



COMPATIBLE NOZZLE

Nozzle Foam

(note: price exclude)